

Arena 700

TOWED DUSTER LT 700:

- Separation of the air flow from product supply
- Product homogeneity
- Balance between accuracy and consistency of performance
- Hydraulic opening and closing

A GAUGE TECHNIQUE THAT DOES NOT ACCEPT COMPROMISE
STAINLESS RANGE FOR TRACTORS \geq CV 60 - 44 KW

Also designed for use in fertilizer distribution both granular and pelleted
ENAMA certification N°05F.001



Basic standard equipment with:

- Tubular steel frame, towing drawbar
- Rubberising 10.0/80-12
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Centrifugal closed blade fan in sheet steel Ø 500 mm, rotation speed 4.090 rpm, 10.500 mc/h
- Tank It. 700 with sheet steel cover; mixer tub, stirrer conveyor, lump breaker, and stainless steel dispenser
- Autonomous and separate delivery of the flow of air and dust
- Flow regulator via shutter and graduated scale
- Hydraulic opening-closing control
- Pair of light guns + additional air silencers

BASIC STANDARD EQUIPMENT

ARENA.700	Tank It. 700 made of steel 10.0/80 Rubberising 10.0/80 – 12
------------------	---

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.64	Universal joint cv 60-1000 mm
ACCESS.51	Universal constant-velocity joint cv 60-1000 mm

MODEL	minimum height	standard height	variable height	width	length	weight
Arena	145 cm	145 cm	-	120 cm	240 cm	450 kg