

# Fast 55

## LT 400 - LT 600

MOUNTED LOW VOLUME ATOMIZER  
STAINLESS RANGE FOR TRACTORS  $\geq$  CV 60 - 44 KW



## Basic standard equipment with:

- Frame in hot galvanized tubular steel treated with high-grip base, metallic paint and transparent protection, predisposed for a pair of wheels
- Tank in high density polyethylene lt. 400 or lt. 600 complete with product mixer, level indicator, plant washing and handwashing tank
- Stainless steel distribution devices with vertical movement of 70°
- Fan housing made of hot galvanised sheet steel and painted
- Centrifugal closed blade fan in sheet steel Ø 550 mm, air volume up to 22000 mc/h, speed up to 120 m/sec
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min. 0-6 bar
- 2 Solenoid valves with remote electrical control, pressure gauge and manual pressure regulator
- Litre-counter dispensers with graduated scale in stainless steel for each sector

### BASIC STANDARD EQUIPMENT





FAST.55.400	Tank lt. 400 in high density polyethylene
FAST.55.600	Tank lt. 600 in high density polyethylene

### ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.08	Universal joint cv 60-700 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.02	Pair of wheels with hubs
ACCESS.70.V	4 V.M.A. solenoid valves to control liquid opening-closing
ACCESS.70.A	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.56	Hydraulic movement of the upper distribution devices equipped with hydraulic lines with quick coupling
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow



## DISTRIBUTION DEVICES AND LITRE-COUNTER DISPENSERS WITH GRADUATED SCALE STAINLESS STEEL WITH ANTIDRIP DEVICE

	2V.F55	2 lower fans (8 sectors in stainless steel)
	2C2V.F55	2 upperguns 2 lower fans (8 sectors in stainless steel)
	4V.F55	2 upper fans (8 sectors in stainless steel) 2 lower fans (8 sectors in stainless steel)
	3T.F55	Vertical movement hydraulic gun with 3 dispensers and hydraulic lines
	3TG.F55	Vertical and swivel movement hydraulic gun with 3 dispensers and hydraulic lines

## NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT



MODEL	minimum height	standard height	variable height	width	length	weight
Fast 55	130 cm	230 cm	-	115 cm	150 cm	325 kg