

LOW VOLUME ARTICULATED ATOMIZER Distribution system for treatments on orchards, olive groves and tall trees

STAINLESS RANGE FOR TRACTORS ≥ CV 75 - 55 KW LT 1000 - LT 1500 - LT 2000

Basic standard equipment with:

- Frame in hot galvanized tubular steel treated with high-grip base, metallic paint and transparent protection
- Central and side protection, height-adjustable hubs
- Steering capability 220°
- High density polyethylene tank lt. 1000 lt. 1500 or lt. 2000 complete with product mixer, level indicator, handwashing tank, circuit washing and can washing
- Stainless steel distribution devices with vertical movement of 70°
- · Metal mesh protective net against foliage intake
- Fan housing made of hot galvanised sheet steel and painted
- Ultra-high performance centrifugal closed blade fan in sheet steel Ø 550 mm, air volume up to 26000 mc/h
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- · Disengagement and centrifugal clutch on the fan shaft
- Anodised aluminium 3 membrane pump, flow rate 130 lt/min, 20 bar
- 2 solenoid valves with electrical remote control, pressure gauge and manual pressure regulator
- Litre-counter dispensers with graduated scale in stainless steel for each sector

BASIC STANDARD EQUIPMENT

HEVEA.1000	Tank lt. 1000 Rubber 10.0/80 – 12
HEVEA.1500	Tank lt. 1500 Rubber 10.0/75 – 15.3
HEVEA.2000	Tank lt. 2000 Rubber 10.0/75 – 15.3

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.52	Universal joint cv 60-700 mm
ACCESS.70.V4	4 V.M.A. solenoid valves to control liquid opening-closing
ACCESS.70.A4	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.EL	Electrostatic system for the positive charge of the treatment
	flow
OMOLOGAZIONE.POWER	Classification for road circulation, full load, with direct coupling
	to the tractor (special drawbar, lights, foot rest, license plate
	holder)

NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT





MODEL	minimum height	standard height	variable height	width	length	weight
Hevea	150 cm	240 cm	-	130 cm	135 cm	330 kg