



MULTI ROW




best sprayer- top of quality
available models: 1000lt
- 1500lt - 2000lt



Standard equipment

	Tank	Rubberising
Power Multi Row 1000	Lt. 1000	10.0/75 - 15.3
Power Multi Row 1500	Lt. 1500	10.0/75 - 15.3
Power Multi Row 2000	Lt. 2000	10.0/75 - 15.3

Technical data: tank's measures

	1000lt	1500lt	2000lt
			
Minimum height	148 cm	136 cm	153 cm
Standard height	148 cm	136 cm	153 cm
Width	142 cm	148 cm	148 cm
Length	195 cm	250 cm	250 cm
Weight	230 kg	295 kg	320 kg

Technical data: sprayer's measures

	Minimum height	Standard height	Width	Length	Weight
Multirow S.	220 cm	280 cm	220 cm	145 cm	580 kg
Multirow D.	220 cm	280 cm	230 cm	142 cm	600 kg

Technical data: components




Required power \geq

CV 75 - 55KW



Fan

Diameter 550mm
4100 giri/min
22.000 m³/hr



Low pressure pump

Maximum flow 135lt/min
Maximum pressure 20 bar

Power Multirow: accessories on request ordered and installed at the origin

ACCESS.52	Universal joint cv 60-700 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.24	Kit version Toscana: steel central and side moulding, adjustable-height hubs, rubberising 10.0/75-15.3
ACCESS.25	Electrical pressure regulator with remote control
ACCESS.26.M	4-way electronic computer for automatic feed control provided with membrane pump
ACCESS.41	Rubberising difference 400/60 - 15.5 to 6 holes
ACCESS.63	Puncture treatment for pair of wheels
ACCESS.69	6-fan columns with independent closing the air and the liquid
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow

