

California NM 600

LOW VOLUME TOWED ATOMIZER STAINLESS
RANGE FOR TRACTORS \geq CV 50 - 37 KW



Basic standard equipment:

- Hot galvanised steel frame treated with high-grip base, Metallic and protective transparent paint
- Central and side protection, height-adjustable hubs
- High density polyethylene tank It 600 complete with product mixer, level indicator, circuit washing tank
- Stainless steel distribution devices
- Fan housing made of hot galvanised sheet steel and painted
- Centrifugal fan made of sheet steel Ø 500 mm
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Centrifugal pump, 200 l/min, 0.6 bar
- 2 solenoid valves with electrical remote control for opening/closing the liquid
- Litre-counter dispensers with graduated scale in stainless steel for each sector


BASIC STANDARD EQUIPMENT

NM.600	Tank It. 600 in high density polyethylene Rubberising 185/65 – 14
---------------	---

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.04	Universal joint cv 40-1000 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow

DISTRIBUTION DEVICES AND LITRE-COUNTER DISPENSERS WITH GRADUATED SCALE STAINLESS STEEL WITH ANTIDRIP DEVICE

	2V.NM50	2 lower fans (8 sectors in stainless steel)
---	---------	---

NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT



MODEL	minimum height	standard height	variable height	width	length	weight
NM 600	140 cm	140 cm	-	115 cm	280 cm	345 kg