

Pony 150

A GAUGE TECHNIQUE THAT DOES NOT
ACCEPT COMPROMISE
STAINLESS RANGE FOR TRACTORS \geq CV 35 - 25 KW

CARRIED DUSTER LT 150:

- Separation of the air flow by the product supply
- Product homogeneity
- Balance between accuracy and consistency of performance
- Manual opening and closing



Basic standard equipment with:

- Polyethylene tank lt.150
- Fan housing made of hot galvanised steel and painted
- Centrifugal closed blade fan in sheet steel ø 450 mm, rotation speed 3.294 rpm
- Autonomous and separate delivery of the flow of air and dust
- Stirrer, mechanical conveyor
- flow regulator via shutter and graduated scale
- Distribution selection control left - total - right
- Power required for power takeoff CV 10 - 7 KW

BASIC STANDARD EQUIPMENT

PONY.150	Tank lt. 150 in polyethylene
-----------------	------------------------------

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.05	Universal joint cv 40-700 mm
------------------	------------------------------

DISTRIBUTION DEVICES

2V.PONY	Pair of fans
C.PONY	Side gun
CG.PONY	Side gun with hydraulic swivel
C.SR.PONY	Side gun with hydraulic extension for greenhouses



MODEL	minimum height	standard height	variable height	width	length	weight
Pony	130 cm	130 cm	-	90 cm	130 cm	90 kg