

Power 50

LT 1000 - LT 1500 - LT 2000

LOW VOLUME
ARTICULATED ATOMIZER
STAINLESS RANGE FOR
TRACTORS \geq CV 60 - 44 KW



Basic standard equipment with:

- Frame in hot galvanized tubular steel treated with high-grip base, metallic paint and transparent protection
- Steering capability 220°
- High density polyethylene tank lt. 1000, lt. 1500 or lt. 2000 complete with product mixer, level indicator, handwashing tank, circuit washing and can washing
- Stainless steel distribution devices with vertical movement of 70°
- Fan housing made of hot galvanised sheet steel and painted
- Ultra-high performance centrifugal closed blade fan in sheet steel Ø 500 mm, air volume up to 17800 mc/h
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min.
- 2 Solenoid valves with remote electrical control, pressure gauge and pressure regulator
- Litre-counter dispensers with graduated scale in stainless steel for each sector





BASIC STANDARD EQUIPMENT

POWER.50.1000	Tank lt. 1000 Rubberising 10.0/80 – 12
POWER.50.1500	Tank lt. 1500 Rubberising 10.0/75 – 15.3
POWER.50.2000	Tank lt. 2000 Rubberising 10.0/75 – 15.3

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.52	Universal joint cv 60-700 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.24	Kit version Toscana: steel central and side moulding, adjustable-height hubs, rubberising 10.0/75-15.3
ACCESS.25	Electrical pressure regulator with remote control
ACCESS.26.C	4-way electronic computer for automatic feed control provided with centrifugal pump
ACCESS.41	Rubberising difference 400/60 - 15.5 to 6 holes
ACCESS.70.V	4 V.M.A. solenoid valves to control liquid opening-closing
ACCESS.70.A	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.42	Hydraulic movement of the upper distribution devices equipped with hydraulic lines with quick coupling
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow
OMOLOGAZIONE POWER	Classification for road circulation, full load, with direct coupling to the tractor (special drawbar, lights, foot rest, license plate holder)

**DISTRIBUTION DEVICES IN STAINLESS STEEL
PROVIDED WITH LITRE-COUNTER DISPENSERS WITH GRADUATED
SCALE IN STAINLESS STEEL WITH ANTIDRIP DEVICE**

	2V.PW50	2 lower fans (8 sectors in stainless steel)
	2C2V. PW50	2 upper guns 2 lower fans (8 sectors in stainless steel)
	4V. PW50	2 upper fans (8 sectors in stainless steel) 2 lower fans (8 sectors in stainless steel)
	3T. PW50 3TG. PW50	Vertical movement hydraulic gun with 3 dispensers and hydraulic lines Vertical and swivel movement hydraulic gun with 3 dispensers and hydraulic lines

**NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH
GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE
EQUIPMENT**



MODEL	minimum height	standard height	variable height	width	length	weight
Power 50	140 cm	240 cm	-	110 cm	135 cm	295 kg