

# POWER 55.12

LT 1000 - LT 1500 - LT 2000

**ARTICULATED LOW VOLUME ATOMIZER:**  
Variable geometry distribution system allowing for treatments in windier conditions  
Electro-hydraulic controller with remote controls for handling management  
**STAINLESS RANGE FOR TRACTORS  $\geq$  CV 75 - 55 KW**



## Basic standard equipment with:

- Hot galvanised steel frame treated with high-grip base, metallic paint and transparent protection
- Central and side protection, height-adjustable hubs
- High density polyethylene tank complete with product mixer, level indicator, handwashing tank, circuit washing and can washing
- Steering capability 220°
- Pressure gauge and manual pressure regulator
- 2 solenoid valves with electrical remote control for opening/closing
- Fan housing made of hot galvanised sheet steel and painted
- Ultra-high performance centrifugal closed blade fan in sheet steel Ø 550 mm, air volume up to 22000 mc/h
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Self-priming stainless pump with automatic belt tensioner, flow rate 200 lt/min.
- Central distribution device with columns with steerable devices
- Upper distribution devices with electrohydraulic control lattice for: opening, closing, adjusting height, width and vertical direction of diffusers with 70° angle

### BASIC STANDARD EQUIPMENT WITH 1 REAR COLUMN

<b>POWER.55.12.A1000</b>	Tank lt. 1000 Rubber 10.0/75 – 15.3
<b>POWER.55.12.A1500</b>	Tank lt. 1500 Rubber 10.0/75 – 15.3
<b>POWER.55.12.A2000</b>	Tank lt. 2000 Rubber 10.0/75 – 15.3

### BASIC STANDARD EQUIPMENT WITH 2 REAR COLUMNS ONLY FOR ROWS EXCEEDING 2.30 METRES

<b>POWER.55.12.B1000</b>	Tank lt. 1000 Rubber 10.0/75 – 15.3
<b>POWER.55.12.B1500</b>	Tank lt. 1500 Rubber 10.0/75 – 15.3
<b>POWER.55.12.B2000</b>	Tank lt. 2000 Rubber 10.0/75 – 15.3

### ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

<b>ACCESS.52</b>	Universal joint cv 60-700 mm
<b>ACCESS.15</b>	Fill tube (filter and bottom valve)
<b>ACCESS.25</b>	Electrical pressure regulator with remote control
<b>ACCESS.26.M</b>	4-way electronic computer for automatic feed control provided with membrane pump
<b>ACCESS.41</b>	Rubberising difference 400/60 - 15.5 to 6 holes
<b>ACCESS.63</b>	Puncture treatment for pair of wheels
<b>ACCESS.70.V4</b>	4 V.M.A. solenoid valves to control liquid opening-closing
<b>ACCESS.70.A4</b>	4 solenoid valves ARAG to control liquid opening-closing
<b>ACCESS.69</b>	6-fan columns with independent closing the air
<b>ACCESS.ELM</b>	Electrostatic system for the positive charge of the treatment flow
<b>OMOLOGAZIONE.POWER</b>	Classification for road circulation, full load, with direct coupling to the tractor (special drawbar, lights, foot rest, license plate holder)

<b>MODEL</b>	<b>minimum height</b>	<b>standard height</b>	<b>variable height</b>	<b>width</b>	<b>length</b>	<b>weight</b>
Power 55-12	220 cm	280 cm	-	220 cm	140 cm	450 kg