Uruapan/FP 550 LT 1000 - LT 1500 - LT 2000

LOW VOLUME ARTICULATED ATOMIZER Distribution system for treatment of tropical plants STAINLESS RANGE FOR TRACTORS ≥ CV 75 - 55 KW



Basic standard equipment with:

- Frame in treated tubular steel treated with high-grip base, metallic paint and transparent protection
- · Central and side protection, height-adjustable hubs
- Steering capability 220°
- High density polyethylene tank complete with product mixer, level indicator, handwashing tank, circuit washing and can washing
- \bullet Stainless steel distribution devices with vertical movement of 70°
- Metal mesh protective net against foliage intake
- Fan housing made of hot galvanised sheet steel and painted
- Ultra-high performance centrifugal closed blade fan in sheet steel Ø 550 mm, air volume up to 22000 mc/h
- Mechanical step-up gear with oil-bath gears and 2 speed gearbox
- Disengagement and centrifugal clutch on the fan shaft
- Anodised aluminium 3 membrane pump, flow rate 130 lt/min, 20 bar
- 4 solenoid valves with electrical remote control
- · Litre-counter dispensers with graduated scale in stainless steel for each sector

BASIC STANDARD EQUIPMENT

URUAPAN.1000	Tank It. 1000 Rubber 10.0/80 – 12
URUAPAN.1500	Tank It. 1500 Rubber 10.0/75 – 15.3
URUAPAN.2000	Tank It. 2000 Rubber 10.0/75 – 15.3

ACCESSORIES ON REQUEST ORDERED AND INSTALLED AT THE ORIGIN

ACCESS.52	Universal joint cv 60-700 mm		
ACCESS.EL	Electrostatic system for the positive charge of the treatment		
	flow		
OMOLOGAZIONE.POWER	Classification for road circulation, full load, with direct coupling		
	to the tractor (special drawbar, lights, foot rest, license plate		
	holder)		











NEW LITRE-COUNTER DISPENSERS IN STAINLESS STEEL WITH GRADUATED SCALE FOR EACH SECTOR PROVIDED WITH THE EQUIPMENT



MODEL	minimum height	standard height	variable height	width	length	weight
Uruapan	130 cm	220 cm	-	130 cm	135 cm	345 kg